

Flat

Design by Ichiro Iwasaki.

Reference

5950.

Application

Floor Lamps

Installation type

Surface

Description

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Diffuser

Polycarbonate diffuser

Materials

Body: Steel

Base: Steel

Head: Aluminium


Reflector: Aluminum

Finish



5950-10 White (NCS S 0300-N)

Sketch



Electrical characteristics

1 x LED PLATE 7W 400mA



Total 7.0 W



VIBIA



Light source: 2700K CRI >90 1200 lm 171 lm/W

Fixture: 455 lm 51.15 lm/W

Driver included: CC - Constant Current 400 mA 100~240V 50/60Hz

Electronic dimming PUSH

Technical characteristics

- 24V transformer at plug

Physical characteristics

1 Box / 0.50 x 0.72 x 0.72 m. / Vol. 0.2592 m³ /

Gross weight 14.6 kg. / Net weight 12.7 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency : 51.15 lm/W

Coordinate system : CG

Total flux : 455.40 lm

Maximum value : 102.48 cd

Light position : C=90.00 G=175.00

Symmetry on the planes : Asymmetric

Isolux : ceiling

Light position :

X=0.00m Y=0.00m Z=2.50m

