

Dots

Design by Martín Azúa.

VIBIA

Reference

4662.

Application

Wall Lamps

Installation type

Surface

Description

The Dots reading lamp is a compact, circular wall sconce that offers focused illumination. The luminaire can be turned to direct a cone-shaped beam of light precisely where needed. Available in solid wood from sustainable forests or lacquered in four Chromatica colours. Equipped with switch on the wall plate.

Diffuser

Polycarbonate diffuser

Materials


Body: ABS

Driver box: Aluminum

Finish

-  **4662-13** White Grey L1 (NCS S 1000-N)
-  **4662-27** Brown L1 (NCS S 1505-Y50R)
-  **4662-37** Terra Red (NCS S 4040-Y70R)
-  **4662-47** Green L1 (NCS S 4005-G80Y)
-  **4662-82** White Oak (Natural oak wood)
-  **4662-83** American walnut (Walnut natural wood)

Sketch



Electrical characteristics

1 x LED 5,75W 500mA

Total 5.8 W



Light source: 2700K CRI >90 500 lm 87 lm/W

Driver included: CC - Constant Current 500 mA 220~240V 50/60Hz

Optional dimming: TRIAC

Physical characteristics

1 Box / 0.13 x 0.20 x 0.21 m. / Vol. 0.0054 m³ /
Gross weight 0.7 kg. / Net weight 0.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.



Photometric data

Efficiency : 21.52 lm/W

Coordinate system : CG

Total flux : 170.03 lm

Maximum value : 201.33 cd

Light position : C=90.00 G=22.50

Symmetry on the planes : Symmetrical planes

270-90



Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates



