

Dots

Design by Martín Azúa.

VIBIA

Reference

4675.

Application

Wall Lamps

Installation type

Surface

Description

The Dots ambient lamp is a compact, circular wall sconce that offers diffuse lighting effects. The fixture rests slightly apart from the wall, radiating an indirect glow around its perimeter like a halo. Available in solid wood from sustainable forests or lacquered in four Chromatica colours.

Diffuser







Polycarbonate diffuser

Materials


Body: ABS

Driver box: Aluminum

Finish

-  **4675-13** White Grey L1 (NCS S 1000-N)
-  **4675-27** Brown L1 (NCS S 1505-Y50R)
-  **4675-37** Terra Red (NCS S 4040-Y70R)
-  **4675-47** Green L1 (NCS S 4005-G80Y)
-  **4675-82** White Oak (Natural oak wood)
-  **4675-83** American walnut (Walnut natural wood)

Sketch



Electrical characteristics

1 x LED PLATE 4,5W 500mA

Total 4.5 W



Light source: 2700K CRI >90 400 lm 89 lm/W

Driver included: CC - Constant Current 500 mA 100~240V 50/60Hz

Optional dimming: 1-10 or DALI

Physical characteristics

1 Box / 0.13 x 0.20 x 0.21 m. / Vol. 0.0054 m³ /

Gross weight 0.7 kg. / Net weight 0.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency : 65.93 lm/W

Coordinate system : CG

Total flux : 406.13 lm

Maximum value : 165.51 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m



Certificates



